

# PROSAFE® VPN FIREWALLS

WIRED

NETGEAR® ProSafe® VPN (Virtual Private Network) Firewalls ensure maximum privacy and security with high-level encryption.



MODEL	FVS318	FVS336G	FVS338	FVX538
PRODUCT DESCRIPTION	ProSafe® VPN Firewall 8 with 8 Port 10/100 Mbps Switch	Prosafe® Dual WAN Gigabit Firewall with SSL & IPsec VPN	ProSafe® VPN Firewall 50 with 8 Port 10/100 Mbps Switch & Dial Back-up	ProSafe® VPN Firewall 200 with 8 Port 10/100 Mbps Switch, Dual WAN & 1 Gigabit LAN
FIREWALL	DoS/SPI Firewall	DoS/SPI Firewall	DoS/SPI Firewall	DoS/SPI Firewall
ROUTER	Ethernet NAT Router	Ethernet NAT Router	Ethernet NAT Router	Ethernet NAT Router
DEDICATED VPN TUNNELS	8	25 (IPsec) / 10 (SSL)	50	200
SWITCH PORTS & INTERFACES	(8) 10/100 Mbps LAN (1) 10/100 Mbps WAN	(4) 10/100/1000 Mbps LAN (2) 10/100/1000 Mbps WAN	(8) 10/100 Mbps LAN (1) 10/100 Mbps WAN (1) Serial Port	(8) 10/100 Mbps LAN (1) 10/100/1000 Mbps LAN (2) 10/100 Mbps WAN (1) Serial Port
WAN FAILOVER		•	•	•
DMZ PORT	SW Port Forwarding	SW Port Forwarding	SW Port Forwarding	•
WIRELESS SUPPORT	N/A	N/A	N/A	N/A
ANTENNA	N/A	N/A	N/A	N/A
WIRELESS ENCRYPTION	N/A	N/A	N/A	N/A
MEMORY (FLASH/DRAM)	2/16MB	16/64MB	16/32MB	16/32MB
3DES THROUGHPUT		16 Mbps	19 Mbps	30 Mbps
CONCURRENT SESSIONS		10,000	10,000	45,000
LAN-TO-WAN THROUGHPUT	11.5 Mbps	60 Mbps	75 Mbps	80 Mbps
WAN LOAD BALANCING		•		•
USER SUPPORT	15 User Network	50 User Network	25 User Network	100 User Network
NAT/PAT	•	•	•	•
QoS	•	•	•	•
NTP SUPPORT	•	•	•	•
CLASSICAL ROUTING MODE	•	•	•	•
DHCP CLIENT/SERVER	•	•	•	•
STATIC IP ASSIGNMENT	•	•	•	•
STATIC ROUTING, DYNAMIC ROUTING	•	•	•	•
IPSec, L2TP, and PPTP VPN PASSTHROUGH	•	•	•	•
VPN PROTOCOLS SUPPORTED	IPSec ESP, AH	IPSec ESP, SSL	IPSec ESP	IPSec ESP
IKE AUTHENTICATION (Pre-Shared Key, Certificates)	•	•	•	•
IPSEC ENCRYPTION	256-bit AES, 168-bit 3DES IPsec	256-bit AES, 168-bit 3DES, 56-bit DES	256-bit AES, 168-bit 3DES IPsec	256-bit AES, 168-bit 3DES IPsec
LOGGING & MONITORING, POLICIES & SCHEDULES, URL CONTENT FILTERING	•	•	•	•
EMAIL NOTIFICATIONS (Built-in-Alerts, Log)	•	•	•	•
REMOTE LOGGING	SYSLOG	SYSLOG	SYSLOG	SYSLOG
SNMP	v1	v2c	v1	v1
BROWSER-BASED CONFIGURATION	•	•	•	•
VPN S/W COMPATIBLE (VPN01L / 05L)	•	•	•	•
NETWORKING MGMT S/W COMPATIBLE (NMS100)		•	•	•
COMPATIBLE ANTENNAS	N/A	N/A	N/A	N/A
PHYSICAL DIMENSIONS	(W x D x H) 253 x 181 x 35 mm (25.3 x 18.1 x 3.5 in.) Weight: 0.935 kg (2.1 lb)	(W x D x H) 254 x 178 x 39.6 mm (10 x 7 x 1.56 in.) Weight: 1.7 kg (3.7 lb)	(W x D x H) 254 x 178 x 39.6 mm (10 x 9 x 1.56 in.) Weight: 1.7 kg (3.7 lb)	(W x D x H) 330 x 203 x 44 mm (13 x 8 x 1.75 in.) Weight: 2.01 kg (4.42 lb)
IN THE BOX	Power adapter, Ethernet cable, Installation guide, Resource CD, Warranty/support info		Ethernet cable, Rackmount kit (FVX538 only), Installation guide, Resource CD with software, Warranty/support info	
WARRANTY	Hardware: Lifetime Power Supply: 3 Year	Hardware: Lifetime Power Supply: 3 Year	Hardware: Lifetime Power Supply: 3 Year	Lifetime
PROSUPPORT MAINTENANCE PKGS - ONCALL 24X7 - XPRESSHW	PMB0331 PRR0331	PMB0331 PRR0331	PMB0331 PRR0331	PMB0331 PRR0331